

12 VOLT DC VIBRATORS



The DC-60 is our smaller vibrator for screens on concrete pumps. It is watertight and ideal for spreaders, sanders and fertilizer hoppers. With 3600 RPM and 60 lbs. of force it comes either in lightweight aluminum or cast iron housings.

DC-100

Perfect size and force for small aggregate hoppers up to 1-1/2 yds. and tailgate spreaders. 100 lbs. of force at 4000 RPM and 12 amperes. For larger hoppers & spreaders use Model DC-450 or DC-700.

CRETE PUMP

Putzmeiste

BRATORS

DC-300 &

SPREADER

BRATORS

DC-500
DC-300 produces up to
400 lbs. of force and
DC-500 up to 450 lbs.
both at 4000 RPM.
Rated for continuous duty.
Both units are ideal for
concrete pumps to keep
concrete flowing through the

screen uninterrupted and to screen off large aggregates that won't go through the pump. DC-500 is totally enclosed and watertight to withstand pressure hose cleanup. DC-300 is totally enclosed. Both units can also be used on concrete chutes, hoppers and spreaders, etc.

CONCRETE PUMP & SCREEN VIBRATORS

12 VOLT DC VIBRATORS



small dump bodies. Picture shows DC-1600 on street sweeper used to shake mud and sand out of hopper.





FOR FAST, SAFE & COMPLETE DISCHARGE OF STICKY OR WET MATERIALS

PLUS VALUES:


- Eliminate destructive slamming of brakes, jerking of hoists, and banging tailgates and reduce expensive damage on brakes, transmissions, clutches, tailgates and rear ends.
- 2. Increase the number of loads hauled and dumped per day.
- 3. Insure a complete, clean dump every time.
- Spread while dumping, reducing manpower and machine time.
- Minimize the tip-over problem
 by allowing discharge at
 lower dumping angles.



WASTE HAULING TRUCKS

"The Best in the Industry"

- DC-3500 for trucks over 10 cu. yd., 22,400-48,000 lbs. load; multi-axle dump trucks and trailers.
- DC-3500-1000 for dump body trucks up to 3 cu. yd. or 7000-15,000 lbs. load; bulk-feed truck hoppers.
- DC-3500-2900 for up to 10 cu. yd. or 18,900-40,500 lbs. load; tandem axle dump trucks.




TECHNICAL DATA


Model	lbs. Force N		Amps.**	Volts	Ph.	Max. Speed	dB*	lbs. We	Duty Cyc	
DC-20	20	89	3.7	6 & 12 DC	1	3500	68	3	1.4	Cont.
DC-50	50	223	3	12 & 24 DC	1	3600	71	6	2.72	Cont.
DC-60	60	267	3	12 & 24 DC	1	3600	68	8**	3.6	Cont.
DC-100	100	445	12	12 & 24 DC	1	4000	72	4	1.8	Cont.
DC-200	300	1334	14	12 & 24 DC	1	4000	73	8	3.6	Cont.
DC-300	350	1557	16	12 & 24 DC	1	4000	74	9	4.0	Cont.
DC-450	400	1780	22	12 & 24 DC	1	7000	75	17	7.7	Cont.
DC-500	450	2005	16	12 & 24 DC	1	4000	73	12	5.5	Cont.
DC-700	700	3115	25	12 & 24 DC	1	6000	75	20	9.1	Int.
DC-900	600	2669	30	12 & 24 DC	1.	6000	78	20	9.1	Special
DC-1600	1000	4450	32	12 & 24 DC	1	5000	82	30	13.6	Special
DC-3500	3500	15572	60	12 & 24 DC	1-	4000	70	36	16.3	Special


NOTE: The frequency will vary with the load. **Amps shown for 12 volt DC (24 volt amps 1/2 of 12 volts)


*Decibel on A-scale at 3' (1 meter)

N = Centrifugal force in Newton.












DC-200, DC-300, DC-900 & DC-1600

DC-20, DC-50 & DC-100 0 VIBCO DC-450 & DC-700







DC-3500

DIMENSIONS

Model	L inch/mm		W inch/mm		H inch/mm		A Inch/mm		B inch/mm		C* Inch/mm		D inch/mm		E inch/mm		
DC-20	5	127	5	127	31/4	89	4	102	-		3/6	10	3	76	3/8	-	10
DC-50	51/4	143	5	127	31/4	64	4	102			3/0	10	21/2	64	3/6		10
DC-60	63/6	162	41/2	114	31/4	83	31/6	64	15/1e	33	5/16	8	3	76	3/8		10
DC-100	63/4	171	6	152	41/4	108	5	127	_		3/6	-10	33/6	86	-		
DC-200	81/2	216	41/6	105	5	127	3	76	51/4 145		8/16	8	3%s	90	_		
DC-300	9	229	41/6	105	5	127	3	76	51/4 145		15/16	8	3%	90			
DC-450	81/4	210	47h	124	41/4	105	31/2	89			1/2	12	4	102	61/2 16		165
DC-700	73/4	197	55%	143	51/4	133	41/2	114			1/2	12	51/he	128	61/2 16		165
DC-500	9	229	61/4	159	51/2	140	51/4	133	4% 114		7/16	_ 11	-	_		_	
DC-900	111/6	283	51/2	140	61/4	160	31/2	89	6% 168		1/2	12	4	102			
DC-1600	111/4	286	5%	143	61/4	159	41h	114	7 178		1/2	12	41/6	184	-		
DC-3500	12	305	10	254	9	229	81/2	216	_		3/4	19	3	76	_		

^{*}Bolt Size NOTE: Dimensions and Technical Data subject to change without notice.

WE ALSO SUGGEST:

HYDRAULIC VIBRATORS







VIBCO hydraulic models are low cost alternatives that provide high force at low frequencies. Built for continuous duty with specially designed motors that last longer than standard hydraulics, these workhorses operate in any position. Best for the toughest unloading jobs and moving materials in huge bins and hoppers.

PNEUMATIC PISTON VIBRATORS






WHEN CONSIDERING PNEUMATIC UNITS. **BE SURE YOU HAVE** THE PROPER AMOUNT OF **LUBRICATED AIR FLOW** (CFM - CUBIC FEET PER MINUTE) AND AIR PRESSURE (PSI - POUNDS PER SQUARE INCH) TO PROPERLY POWER THE UNIT.

Choose pneumatic piston style vibrators for applications that need high impact linear force. Built to move even the most stubborn, sticky material you have, these units can take the abuse and will last a long time with the proper lubricated air supply. Flange mounted with industry standard bolt patterns for easy exchangeability.

ASK ABOUT A FREE TRIAL



CAT. #9803 Vibrators for Sand & Gravel

VIBEG



CAT #9808 **Plate Compactors** & Rollers



CAT. #9511C Big Bertha Dump **Body Vibrators**



CAT. #9001C General Catalog

ADDITIONAL **PRODUCT BROCHURES ASK FOR** YOUR FREE COPIES

TODAY



Corporate HQ & Factory: 75 Stilson Road, P.O. Box 8 Wyoming, RI 02898

Mail: vibrators@vibco.com Phone: (401) 539-2392 (800) 633-0032 (401) 539-2584 FAX:

Western US:

Phoenix, AZ 85254 Phone: (480) 596-1809

(800) 633-0032 FAX: (480) 596-1614

Southeastern US:

Charlotte, NC 28277 Phone: (401) 539-2392 (800) 633-0032 (401) 539-2584

Canada:

2215 Dunwin Drive Mississauga, ONT L5L 1X1 Phone: (905) 828-4191 (800) 465-9709 FAX: (905) 828-5015

We're The Vibrator Guys.™

PRINTED IN USA 9112C @2005 VIBCO, INC.